

## Armrests

- Stable, ergonomically shaped armrests with curved support surface (350 x 120 mm)
- Height-adjustable and equipped with a ball joint for 360-degree rotation
- Designed for personalized adjustment to the surgeon
- Optionally available with one-hand release
- Optionally available with linear guide and one-hand release



## Chassis

- 4 high-quality, smooth-running double castors
- 5th castor for added resistance to tipping
- Optimized foot space
- Central braking system effective on 4 castors
- Integrated foot keypad panel for seat height adjustment
- Power supply-independent battery box with emergency stop button



## Technical specifications

### Lifting column

- Drive 3,000 N (IPX4)
- Lifting height 200 mm

### Chassis

- L x W (incl. braking system/foot keypad) 650 x 600 mm
- Castors  $\varnothing$  100 mm
- 5th castor  $\varnothing$  65 mm
- Central brake acting on all four castors
- Emergency stop button

### Battery unit

- Battery box with 2 batteries (lead-gel), pollution free, maintenance-free, cadmium-free 2 x 12 V, 7.2 Ah
- Universal battery charger: Input: 100 – 240 V  
Output: 30 V

### Seating systems:

### Comfort | Dynamic

- Min. sitting height 550 mm | 600 mm
- Max. sitting height 750 mm | 800 mm
- Seat angle adjustments  $-5^{\circ}/+5^{\circ}$  |  $-12^{\circ}$
- Back angle adjustments  $-25^{\circ}/+5^{\circ}$  |  $-16^{\circ}$

### Weight

45 kg

### Max. load

150 kg

Subject to technical modifications.

## Technical dimensions

### Seating system Comfort

#### Minimum



Specifications in mm

#### Maximum



### Seating system Dynamic

#### Minimum



#### Maximum

